

BULK MATERIAL DISCHARGE HOSE

MANDREL

Application: Softwall hose designed for delivery of dry cement, sand, gravel and etc. Equipped with excellent rebounds, durability and abrasion resistant properties.

Temperature: -40°C (-40°F) to +80°C (+176°F)




Tube: Black, smooth, conductive natural rubber, abrasion resistant.

Reinforcement: High strength synthetic cord.

Cover: Black, smooth (wrapped finish), synthetic rubber, weathering resistant.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/4"	19.1	29.0	10	150	30	450	61	200
1"	25.4	36.0	10	150	30	450	61	200
1-1/4"	31.8	42.0	10	150	30	450	61	200
1-1/2"	38.1	49.0	10	150	30	450	61	200
1-3/4"	44.5	56.0	10	150	30	450	61	200
2"	50.8	63.0	10	150	30	450	61	200
2-1/2"	63.5	76.0	10	150	30	450	61	200
3"	76.2	89.0	10	150	30	450	61	200
4"	101.6	118.0	10	150	30	450	61	200
5"	127.0	145.0	10	150	30	450	61	200
6"	152.4	170.0	10	150	30	450	61	200
8"	203.2	225.0	10	150	30	450	61	200

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber