

CHEMICAL DISCHARGE HOSE

MANDREL

Application: Softwall hose designed for delivery of a wide range of chemical products, sewage system and filtration plants.

Temperature: -30°C (-22°F) to +65°C (+149°F)



Tube: White, smooth, EPDM rubber.


Reinforcement: High strength synthetic cord.

Cover: Blue, smooth (wrapped finish), EPDM rubber.

Optional Request: Anti-static wire.

Remarks: Refer **Chemical Resistance Chart** for details.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/4"	19.1	31.0	16	240	48	720	61	200
1"	25.4	37.0	16	240	48	720	61	200
1-1/4"	31.8	44.0	16	240	48	720	61	200
1-1/2"	38.1	51.0	16	240	48	720	61	200
2"	50.8	66.0	16	240	48	720	61	200
2-1/2"	63.5	79.0	16	240	48	720	61	200
3"	76.2	92.0	16	240	48	720	61	200
4"	101.6	120.0	16	240	48	720	61	200
5"	127.0	145.0	16	240	48	720	30	100
6"	152.4	172.0	16	240	48	720	30	100

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber