

# DOCK HOSE

MANDREL

**Application:** Heavy duty suction and delivery hose designed for transferring petroleum product from tankers and barges, bunkering service and industrial applications. Suitable for aromatic content up to 50%.

**Temperature:** -40°C (-40°F) to +82°C (+180°F)








**Tube:** Black, smooth, nitrile rubber.

**Reinforcement:** High strength synthetic cord, dual helix wires and anti-static wires.

**Cover:** Black, smooth (wrapped finish), neoprene rubber, oil, fuel, sea water and weathering resistant.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 <b>I.D.</b>		 <b>O.D.</b>	 <b>Work Pressure</b>		 <b>Burst Pressure</b>		 <b>Max. Length</b>	
inch	mm	mm	bar	psi	bar	psi	m	ft
3"	76.2	96.0	17	255	68	1020	61	200
4"	101.6	126.0	17	255	68	1020	61	200
5"	127.0	155.0	17	255	68	1020	61	200
6"	152.4	185.0	17	255	68	1020	61	200
8"	203.2	242.0	17	255	68	1020	40	130
10"	254.0	298.0	17	255	68	1020	12	40
12"	304.8	350.0	17	255	68	1020	12	40

## Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber