

DUST COLLECTOR SUCTION HOSE

MANDREL

Application: Light weight corrugated hose designed for the extraction of waste dust, fumes, light particles and etc.

Temperature: -40°C (-40°F) to +80°C (+176°F)




Tube: Tan, smooth, natural rubber, abrasion resistant.

Reinforcement: High strength synthetic cord and helix wire.

Cover: Tan, corrugated (wrapped finish), synthetic rubber, weathering resistant.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/4"	19.1	27.0	6	90	18	270	61	200
1"	25.4	34.0	6	90	18	270	61	200
1-1/4"	31.8	40.0	6	90	18	270	61	200
1-1/2"	38.1	47.0	6	90	18	270	61	200
2"	50.8	60.0	6	90	18	270	61	200
2-1/2"	63.5	73.0	6	90	18	270	61	200
3"	76.2	86.0	6	90	18	270	61	200
3-1/2"	88.9	99.0	6	90	18	270	61	200
4"	101.6	114.0	6	90	18	270	61	200
4-1/2"	114.3	126.0	6	90	18	270	61	200
5"	127.0	140.0	6	90	18	270	61	200
6"	152.4	166.0	6	90	18	270	61	200
8"	203.2	218.0	6	90	18	270	61	200
10"	254.0	270.0	6	90	18	270	12	40
12"	304.8	321.0	6	90	18	270	12	40

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber