

HOT WATER DISCHARGE HOSE

MANDREL

Application: Softwall hose designed for conveyance of high temperature water for automotive, cleaning and cooling applications.

Temperature: -30°C (-22°F) to +100°C (+221°F)




Tube: Black, smooth, EPDM rubber.

Reinforcement: High strength synthetic cord.

Cover: Black, smooth (wrapped finish), EPDM rubber.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
1/2"	12.7	22.0	10	150	30	450	61	200
3/4"	19.1	31.0	10	150	30	450	61	200
1"	25.4	37.0	10	150	30	450	61	200
1-1/4"	31.8	44.0	10	150	30	450	61	200
1-1/2"	38.1	50.0	10	150	30	450	61	200
2"	50.8	64.0	10	150	30	450	61	200
2-1/2"	63.5	77.0	10	150	30	450	61	200
3"	76.2	90.0	10	150	30	450	61	200
3-1/2"	88.9	104.0	10	150	30	450	61	200
4"	101.6	118.0	10	150	30	450	61	200

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber