

MARINE FUEL SUCTION HOSE

MANDREL

Application: Hardwall hose designed for delivery of gasoline or diesel fuel aboard small craft including pleasure craft.

Temperature: -25°C (-13°F) to +100°C (+212°F)




Tube: Black, smooth, synthetic rubber.

Reinforcement: High strength synthetic cord and helix wire.

Cover: Black, smooth (wrapped finish), synthetic rubber, weathering and fire resistant.

Optional Request: SAE J1527-A2, ISO 7840-A2 USCG.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
1-1/2"	38.1	48.0	10	150	30	450	61	200
1-5/8"	41.3	52.0	10	150	30	450	61	200
1-7/8"	47.6	60.0	10	150	30	450	61	200
2"	50.8	63.5	10	150	30	450	61	200
2-3/8"	60.3	73.0	10	150	30	450	61	200
2-1/2"	63.5	77.0	10	150	30	450	61	200
3"	76.2	90.0	10	150	30	450	61	200

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber