

MARINE FUEL HOSE

EXTRUSION

Application: Designed for delivery of fuel oil or diesel fuel aboard small craft including pleasure craft.

Temperature: -25°C (-13°F) to +100°C (+212°F)



Tube: Black, smooth, synthetic rubber.

Reinforcement: High strength synthetic yarn.

Cover: Black, smooth, synthetic rubber, weathering and fire resistant.

Optional Request: SAE J1527-A1, ISO 7840-A1 USCG.
SAE J1527-A2, ISO 7840-A2 USCG.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

I.D.		O.D.	Work Pressure		Burst Pressure		Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
1/4"	6.4	15.8	3.5	50	14	200	100	330
5/16"	7.9	17.5	3.5	50	14	200	100	330
3/8"	9.5	20.0	3.5	50	14	200	100	330
1/2"	12.7	24.0	3.5	50	14	200	100	330
5/8"	15.9	27.0	3.5	50	14	200	100	330
3/4"	19.1	30.0	3.5	50	14	200	100	330
1"	25.4	36.0	3.5	50	14	200	100	330

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber