

MARINE WET EXHAUST HOSE (CORRUGATED)

MANDREL

Application: Light weight and flexible hose designed for delivery of water cooled diesel engine exhaust gas systems installed on a small craft less than 24m in length or pleasure yachts.

Temperature: -30°C (-22°F) to +121°C (+250°F)




Tube: Black, smooth, synthetic rubber.

Reinforcement: High strength synthetic cord and helix wire.

Cover: Black, corrugated (wrapped finish), synthetic rubber, weathering and abrasion resistant.

Optional Request: SAE J2006, Style R2.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/4"	19.1	27.0	3	45	9	135	61	200
7/8"	22.2	31.0	3	45	9	135	61	200
1"	25.4	34.0	3	45	9	135	61	200
1-1/8"	28.6	39.0	3	45	9	135	61	200
1-3/16"	30.2	40.0	3	45	9	135	61	200
1-1/4"	31.8	41.0	3	45	9	135	61	200
1-5/16"	33.3	42.0	3	45	9	135	61	200
1-3/8"	34.9	44.0	3	45	9	135	61	200
1-1/2"	38.1	47.0	3	45	9	135	61	200
1-9/16"	39.7	49.0	3	45	9	135	61	200
1-5/8"	41.3	50.0	3	45	9	135	61	200
1-3/4"	44.5	54.0	3	45	9	135	61	200
1-7/8"	47.6	57.0	3	45	9	135	61	200
2"	50.8	60.0	3	45	9	135	61	200
2-1/8"	54.0	65.0	3	45	9	135	61	200
2-1/4"	57.2	68.0	3	45	9	135	61	200
2-3/8"	60.3	70.0	3	45	9	135	61	200
2-1/2"	63.5	73.0	3	45	9	135	61	200
2-5/8"	66.7	76.0	3	45	9	135	61	200
2-3/4"	69.9	79.0	3	45	9	135	61	200
2-7/8"	73.0	83.0	3	45	9	135	61	200
3"	76.2	86.0	3	45	9	135	61	200
3-1/8"	79.4	90.0	3	45	9	135	61	200
3-1/2"	88.9	100.0	3	45	9	135	61	200
4"	101.6	113.0	3	45	9	135	61	200
4-1/2"	114.3	127.0	3	45	9	135	61	200
5"	127.0	139.0	3	45	9	135	61	200
6"	152.4	165.0	3	45	9	135	61	200
8"	203.2	215.0	3	45	9	135	61	200
10"	254.0	268.0	3	45	9	135	12	40
12"	304.8	320.0	3	45	9	135	12	40

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Colour of Rubber
- Different Length
- Different Pressure