

MULTIPURPOSE OIL HOSE

MANDREL

Application: Designed for various applications, including conveying air, water and oil in mining, agriculture and construction.

Temperature: -20°C (-4°F) to +80°C (+176°F)








Tube: Black, smooth, synthetic rubber.

Reinforcement: High strength synthetic yarn.

Cover: Black, smooth, synthetic rubber, oil and weathering resistant.

Optional Request: Anti-static wire.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/16"	4.8	12.0	20	300	60	900	120	400
1/4"	6.4	13.0	20	300	60	900	120	400
5/16"	7.9	15.0	20	300	60	900	100	330
3/8"	9.5	17.0	20	300	60	900	100	330
1/2"	12.7	21.0	20	300	60	900	100	330
5/8"	15.9	26.0	20	300	60	900	100	330
3/4"	19.1	29.0	20	300	60	900	100	330
7/8"	22.2	32.0	20	300	60	900	100	330
1"	25.4	36.0	20	300	60	900	100	330
1-1/4"	31.8	44.0	20	300	60	900	60	200
1-1/2"	38.1	54.0	20	300	60	900	60	200
2"	50.8	66.0	20	300	60	900	60	200

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber