

TANK TRUCK HOSE

MANDREL

Application: Hardwall hose designed for suction and delivery of a wide range of petroleum fuel with aromatic content up to 50% for tank trucks.

Temperature: -20°C (-4°F) to +80°C (+176°F)








Tube: Black, smooth, nitrile rubber.

Reinforcement: High strength synthetic cord and helix wire.

Cover: Black, corrugated (wrapped finish), synthetic rubber, oil, fuel, and weathering resistant.

Optional Request: Smooth (wrapped finish); Anti-static Wire.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/4"	19.1	29.0	10	150	30	450	61	200
1"	25.4	35.0	10	150	30	450	61	200
1-1/4"	31.8	42.0	10	150	30	450	61	200
1-1/2"	38.1	48.0	10	150	30	450	61	200
2"	50.8	62.0	10	150	30	450	61	200
2-1/2"	63.5	76.0	10	150	30	450	61	200
3"	76.2	89.0	10	150	30	450	61	200
3-1/2"	88.9	103.0	10	150	30	450	61	200
4"	101.6	116.0	10	150	30	450	61	200
5"	127.0	143.0	10	150	30	450	61	200
6"	152.4	170.0	10	150	30	450	61	200
8"	203.2	224.0	10	150	30	450	61	200

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber