

WATER HOSE (10 BAR)

EXTRUSION

Application: Designed for water and non-corrosive fluids used in construction sites and light industrial applications.

Temperature: -30°C (-22°F) to +70°C (+158°F)





Tube: Black, smooth, synthetic rubber.

Reinforcement: High strength synthetic yarn.

Cover: Black, smooth, synthetic rubber, weathering resistant.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/16"	4.8	11.0	10	150	30	450	120	400
1/4"	6.4	12.0	10	150	30	450	120	400
5/16"	7.9	15.0	10	150	30	450	100	330
3/8"	9.5	17.0	10	150	30	450	100	330
1/2"	12.7	20.0	10	150	30	450	100	330
5/8"	15.9	24.0	10	150	30	450	100	330
3/4"	19.1	28.0	10	150	30	450	100	330
7/8"	22.2	31.0	10	150	30	450	100	330
1"	25.4	35.0	10	150	30	450	100	330
1-1/4"	31.8	42.0	10	150	30	450	60	200
1-1/2"	38.1	50.0	10	150	30	450	60	200
2"	50.8	66.0	10	150	30	450	60	200

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber