

CORRUGATED WATER SUCTION HOSE (CUFF END)

MANDREL

Application: Hardwall hose designed for suction and delivery of water, and non-corrosive fluids used in construction sites and light duty industrial applications. Lengths incorporate cuffed ends for ease of fitting insertion.

Temperature: -30°C (-22°F) to +70°C (+158°F)




Tube: Black, smooth, synthetic rubber.

Reinforcement: High strength synthetic cord and helix wire.

Cover: Black, corrugated (wrapped finish), synthetic rubber, abrasion and weathering resistant.

Wellcall recommends using the **STAMPED** process to aid in determining the correct hose for your application.

 I.D.		 O.D.	 Work Pressure		 Burst Pressure		 Max. Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3"	76.2	88.0	10	150	30	450	-	-
4"	101.8	115.0	10	150	30	450	-	-
6"	152.4	168.0	10	150	30	450	-	-
8"	203.2	222.0	10	150	30	450	-	-
10"	254.0	278.0	10	150	30	450	-	-
12"	304.8	328.0	10	150	30	450	-	-

Commonly Available Upon Request:

- Different Diameter
- Different Temperature
- Different Length
- Different Pressure
- Different Colour of Rubber